

Reinco

Power Mulching & Hydrograssing Machinery
Reinco Inc. • PO Box 512 • Plainfield, NJ 07061-0512

Phone (800) 526-7687
Local (908) 755-0921
Fax (908) 755-6379
www.reinco.com

HYDROGRASSER FEATURES COMPARISON

HYDROGRASSER MODEL

CAPACITY	2P	2PA	5H3	5H3A	10GX3	10GX3A	13GX3	15GX3	20GX3	30GX3
WORKING VOLUME (WATER)	200 (757 l)	200 (757 l)	500 (1895 l)	500 (1895 l)	1000 (3785 l)	1000 (3785 l)	1300 (4921 l)	1500 (5678 l)	2000 (7570 l)	3000 (11356 l)
TANK VOLUME (SLURRY)	250 (900 l)	250 (900 l)	625 (2360 l)	625 (2360 l)	1250 (4750 l)	1250 (4750 l)	1550 (5900 l)	1850 (7000 l)	2350 (8900 l)	3500 (13000 l)
GRANULARS (Max) lbs.	80 (40kg)	80 (40kg)	800 (400kg)	800 (400kg)	2500 (1100kg)	2500 (1100kg)	3100 (1400kg)	5000 (2200kg)	6500 (2900kg)	10000 (4535kg)
FIBER MULCH (Max) lbs.	100 (45kg)	100 (45kg)	250 (110kg)	250 (110kg)	500 (200kg)	500 (200kg)	650 (290kg)	750 (340kg)	1000 (453kg)	1500 (700kg)

EFFECTIVE RANGE / FEET

SPRAY BOOM			125 (38m)	125 (38m)	130 (40m)	130 (40m)	130 (40m)	160 (49m)	160 (49m)	160 (49m)
WITH EXTENSION HOSES*	180 (54m)	180 (54m)	250 (76m)	250 (76m)	400 (121m)	400 (121m)	400 (121m)	350 (106m)	350 (106m)	350 (106m)

(*Ratings Offered with Optional Hose Package Carrying Capacities)

DIMENSIONS

LENGTH	4'-2" (1.27m)	11' (3.54m)	8'-1" (2.46m)	15'-0" (4.57m)	12'-4" (3.67m)	19'-6" (5.94m)	12'-3" (3.43m)	14'-6" (4.42m)	16'-7" (5.05m)	18'-10" (5.74m)
WIDTH	2'-9" (.83m)	6'-8" (2.03m)	4'-11" (1.49m)	6'-10" (2.08m)	6'-4" (1.93m)	7'-2" (2.18m)	7'-6" (2.28m)	7'-11" (2.41m)	7'-11" (2.41m)	7'-11" (2.41m)
HEIGHT	3'-7" (1.09m)	5'-3" (1.6m)	6'-7" (2.06m)	8'-0" (2.438m)	8'-0" (2.36m)	10'-2" (2.81m)	7'-10" (2.36m)	8'-2" (2.48m)	8'-1" (2.46m)	8'-10" (2.69m)

WEIGHT

BASIC UNIT (LBS)	775 (351.5kg)	1510 (684.9kg)	1750 (793.8kg)	3500 (1587.6kg)	3500 (1587.6kg)	5500 (2494.8kg)	3800 (1723.8kg)	6000 (2723.6kg)	7000 (3175.2kg)	8500 (3855.5kg)
FULLY CHARGED (LBS)	2735 (1240.6kg)	3470 (1573.9kg)	7000 (3175.9kg)	8500 (3855.5kg)	14350 (6509.0kg)	16350 (7560.2kg)	17600 (7983.2kg)	23800 (10795.5kg)	29700 (13471.7kg)	43500 (19731.3kg)

POWER UNIT

STANDARD ENGINE	BRIGGS I/H	BRIGGS I/H	HONDA GX670	HONDA GX670	KUBOTA V1505B1	KUBOTA V1505B1	KUBOTA V1505B1	JOHN DEERE 4024T270	JOHN DEERE 5030T270	JOHN DEERE 5030T270
HORSEPOWER (kw)	8 6	8 6	20 14.9	20 14.9	33.5 25	33.5 25	33.5 25	66 50.7	99 74	99 74
COOLING	AIR	AIR	AIR	AIR	WATER	WATER	WATER	WATER	WATER	WATER
OPTIONAL ENGINE	HONDA I/H	HONDA I/H								
HORSEPOWER (kw)	8 6	8 6								
COOLING	AIR	AIR								

PUMP

SIZE	3x3	3x4x7	3x4x8 1/4	4x6x10	4x6x10 7/8	4x6x10 5/8
GPM @ PSI	330 @ 30	250 @ 50	400 @ 70	650 @ 115	650 @ 115	750 @ 115
PARTIAL CLEARANCE	1-1/2"	1-1/8"	1-1/8"	1"		
MATERIAL	POLY		ALL IRON	ALL IRON		
BEARING LUBRICATION	OIL		OIL	OIL		
SEAL	MS		DMS	DMS		

FILL ASSEMBLY

ANTI-SIPHONING-STANDARD	2"	2"	2"	2"	2"	2"	2"	2"	2"	2"
STANDARD BRAKES (AIR GAP) OPTIONAL	1-1/2"	1-1/2"	1-1/2"	1-1/2"	2"	2"	2"	2"	2"	2"
(AIR GAP) OPTIONAL	-	-	-	-	-	-	-	3"	3"	3"

MOUNTING

	SKID	TRAILER	SKID	TRAILER	SKID	TRAILER	SKID	SKID	SKID	SKID
AXLE	-	SINGLE	-	SINGLE	-	TANDEM	-	-	-	-
OPTIONAL AXLE	-	-	-	TANDEM	-	-	-	-	-	-
STANDARD BRAKES	-	ELECTRIC	-	ELECTRIC	-	ELECTRIC	-	-	-	-
OPTIONAL BRAKES	-	HYDR	-	HYDR	-	HYDR	-	-	-	-
STANDARD HITCH	-	2" BALL	-	LUNETTE	-	LUNETTE	-	-	-	-
OPTIONAL HITCH	-	LUNETTE	-	2-5/16"	-	2-5/16"	-	-	-	-

TRUCK REQUIREMENTS

RECOMMENDED GVW (Min)	5,000	-	14,000	-	23,000	-	25,000	38,000	44,200	64,000
CAB TO AXLE DIMENSION	-	-	-	72"	-	102"	102"	120"	132"	144"
Tongue Weight EMPTY	-	210	-	670	-	300	-	-	-	-
Tongue Weight CHARGED	-	300	-	1800	-	2700	-	-	-	-

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

HG GX3_T3Comp0209